

## Specifications

| Item                |                      | 26" LCD COLOUR TV,<br>Model: LC-26GA5E  | 32" LCD COLOUR TV,<br>Model: LC-32GA5E                  | 37" LCD COLOUR TV,<br>Model: LC-37GA5E                  |
|---------------------|----------------------|---|---|---|
| LCD panel           |                      | 26" Advanced Super View & BLACK TFT LCD   | 32" Advanced Super View & BLACK TFT LCD                 | 37" Advanced Super View & BLACK TFT LCD                 |
| Number of dots      |                      | 3,147,264 dots (1366 × 768 × 3 dots)  |   |   |
| Video Colour System |                      | PAL/SECAM/NTSC 3.58/NTSC 4.43/PAL 60  |   |   |
| TV Function         | TV-Standard (CCIR)   | B/G, I, D/K, L, L'  |   |   |
|                     | Receiving Channel    | VHF/UHF   | E2-E69ch, F2-F69ch, I21-I69ch, IR A-IR Jch              |   |
|                     |                      | CATV  | Hyper-band, S1-S41ch                                    |   |
|                     | TV-Tuning System     | Auto Preset 99 ch, Auto Label, Auto Sort  |   |   |
| STEREO/BILINGUAL    |                      | NICAM/A2  |   |   |
| FM RADIO Function   | Receiving Frequency: | 87.5-108 MHz  |   |   |
|                     | Receiving Channel:   | 1-40 CH   |   |   |
| Brightness          |                      | 450 cd/m <sup>2</sup>   |   |   |
| Backlight life      |                      | 60,000 hours (at Backlight Standard position)   |   |   |
| Viewing angles      |                      | H : 170° V : 170°   |   |   |
| Audio amplifier     |                      | 10W × 2   |   |   |
| Speakers            |                      | Ø 8 cm 2pcs   |   |   |
| Terminals           | Rear                 | ANTENNA IN  | UHF/VHF 75 Ω Din type                                   |   |
|                     |                      | FM Radio in   | Din type  |   |
|                     |                      | EXT 1   | SCART (AV input/output, RGB input, TV output)           |   |
|                     |                      | EXT 2   | SCART (AV input/output, Y/C input, AV Link)             |   |
|                     |                      | EXT 3   | S-VIDEO (Y/C input), RCA pin (AV input)                 |   |
|                     |                      | EXT 4   | RCA pin (component input)                               |   |
|                     |                      | PC INPUT  | D-sub 15 pin (ANALOG RGB), Ø 3.5 mm Jack (Audio Input)  |   |
|                     |                      | AV OUTPUT   | RCA pin (Variable/Fixed)                                |   |
|                     |                      | Headphones  | Ø 3.5mm jack (Audio output)                             |   |
| OSD language        |                      | English/German/French/Italian/Spanish/Dutch/Swedish/Portuguese/Finnish/Turkish/Greek/Russian/Polish |   |   |
| Power Requirement   |                      | AC 220-240 V, 50 Hz   |   |   |
| Power Consumption   |                      | 110 W (0.95 W Standby)<br>(Method IEC60107)   | 135 W (0.95 W Standby)<br>(Method IEC60107)             | 162 W (0.95 W Standby)<br>(Method IEC60107)             |
| Weight              |                      | 12 kg (Display only),<br>15 kg (Display with stand)   | 15.5 kg (Display only),<br>19.5 kg (Display with stand) | 18.5 kg (Display only),<br>22.5 kg (Display with stand) |

- As a part of policy of continuous improvement, SHARP reserves the right to make design and specification changes for product improvement without prior notice. The performance specification figures indicated are nominal values of production units. There may be some deviations from these values in individual units.

### NOTE

- Refer to inside back cover for dimensional drawings.